

STYLE 200 COMPRESSED SHEET GASKET



Manufactured from synthetic fibers bonded together into a homogenous sheet with an SBR binder, **Style 200** is our most popular compressed sheet. It withstands temperatures up to 750 °F and 399 °C with excellent creep resistance and high torque retention properties. **Style 200** is treated with a clear anti-stick release agent and is recommended for pressures up to 1200 psi. This compressed sheet gasket services water, steam, mild chemicals, and inert gases. Applications include all mating pipe flanges, boilers, manhole and handhold gaskets, pumps, compressors, valves, turbines, mixers and vessels.

SPECIFICATIONS

Style: 200 Compressed Sheet Gasket

Binder: SBR

Color: Black

Pressures: 1200 psi max.

Temperatures: up to 750° F / 399° C

Sizes: 60" x 60"

Thicknesses: 1/64", 1/32", 1/16", 3/32", 1/8", 1/4"

"Since the performance of the gasket material is dependent on many other factors not related to the gasket itself, purchaser is **WARNED** that the maximum operating conditions shown in the Technical Data Chart may not be achieved under the certain conditions. Purchaser is therefore urged to test the gasket material under the actual conditions of assembly and operation to determine the appropriate maximum operating conditions."

This information is based on data that we believe to be reliable. Since conditions of product use are outside of our control, we make no warranties, expressed or implied and assume no liability in connection with any use of this information.

Certified to ISO 9001: 2000 Standards.

Quality Fluid Sealing Solutions for Industry.