

STL-5 Barrier Fluid

Specifically formulated, STL-5 Barrier Fluid from SEPCO Synthetics has no detergents or heavy metals. This high-performance, synthetic barrier fluid is the workhorse of seal lubricants. It meets most barrier and buffer fluid needs within chemical, petrochemical, pipeline, ethanol and other biofuel, and refinery plants. STL-5 is ideal for mechanical seal systems in ethanol production. Available in 5-gallon containers.



FEATURES

- Formulated from the highest quality synthetic base stocks
- FDA compliant
- ISO_VG32
- The additives provide a non-reactive stable fluid for seal service across an extremely wide temperature range
- Excellent low-temperature fluidity and high-temperature stability
- Resists thermal and oxidative degradation
- Environmentally safe and readily biodegradable
- Low moisture content
- Excellent heat transfer
- Wide seal compatibility range
- Provides longer seal life

OPERATING PARAMETERS

- Viscosity
 - At 40°C = 30.5 cSt
 - At 100°C = 5.9 cSt
- Max temperature: 460°F (238°C)
- Specific gravity: 0.827

Certified to ISO 9001:2015 Standards

This information is based on data that we believe to be reliable. Since conditions of product use are outside of our control, we make no warranties, expressed or implied and assume no liability in connection with any use of this information.
V030121